



GE LED 35W HID Lamp



The 35W LED HID lamp from GE offers a safe, cost effective and energy efficient alternative to HID Mercury lamps for outdoor and industrial applications. Direct replacement solution for both 80W Mercury Vapour (MV) and 125W HID lamps.

| RANGE SUMMARY | |
|---------------|--|
| S13203L | GE LED 35W HID LAMP E27 4000K 4,800LM 50,000HRS 220-240V CRI ≥71 |
| S13202L | GE LED 35W HID LAMP E27 3000K 4,800LM 50,000HRS 220-240V CRI ≥71 |
| S70451R | GE LED 30W 2 CCT HID E27 3000K, 4000K |

SPECIFICATIONS

| MEASUREMENTS | |
|----------------------|--------------------------|
| PRODUCT DIMENSIONS | |
| Unit Size (cm) | H 16.9 x W 7.6 |
| Weight (g) | 0.35 |
| PACKAGING DIMENSIONS | |
| Retail Pack Size | 84 x 84 x 193 |
| Weight | 0.43 |
| Retail Barcode (EAN) | 9333509132035 |
| Quantity | 1 |
| Inner Pack Size (cm) | L 29.2 x W 19.2 x D 21.0 |
| Weight | 2.82 |
| Inner Barcode (GTIN) | 29333509132039 |
| Quantity | 6 |
| Outer Pack Size | L 40.5 x W 30.6 x D 45.0 |
| Weight (kg) | 12 |
| Outer Barcode (GTIN) | 39333509132036 |
| Quantity | 24 |

| TECHNICAL DATA | |
|--------------------|----------------|
| Voltage | 220 - 240V |
| Wattage (Max) | 35W (Max 38.5) |
| Socket Type | E27 |
| Beam Angle | 280 |
| Brightness/Lumens | 4800 |
| Light Appearance | 4000K / 3000K |
| Efficacy (LM/W) | 137 |
| CRI | >71 |
| Average Rated Life | 50,000 hours |

Note 1: It is advisable to connect this lamp within an enclosure with a degree of ingress protection of at least IP54 or higher.

Note 2: Not suitable for dimming.

Note 3: Whilst this lamp can be a direct 80W or 125W mercury lamp replacement, for non metered public streetlighting usage AEMO require the original ballast to be removed from the circuit.